

KRATKI JAS

The Kratki JAS is an excellent value-for-money fireplace, ideal for installations where the unit is displayed exposed on a ledge or placed exposed inside an open fireplace cavity. Its compact 35 cm depth makes it a perfect solution for shallow hearths or limited spaces.

When built into a wall, you can pair it with the convection box and frame system (sold separately) - or, for a more complete built-in fireplace solution, consider the Kratki ildnord Alta.

This wood-burning offers a generous, unobstructed view of the flames through its large rectangular glass window.

Categories: All fireplaces, Bestselling wood inserts, Built-in wood fireplaces, Wood fireplaces
Tags: Closed-combustion, Compact, Heat intensifying ceramics, Modern

PRODUCT GALLERY















ADDITIONAL INFORMATION

Weight	82 kg
Dimensions	71.1 × 34.6 × 54.3 cm
CO emissions	0.15%
Colour	Black
Country of manufacture	Poland
Efficiency	71%
Flue pipe diameter	150mm
Fuel	Wood
Heat output	10 kW
Heating capacity	150 – 250m3
Material	Steel
Warranty	10-year warranty
Combustion technology	Primary and secondary combustion
Door	Standard door
Flue exit	Top

PRODUCT DESCRIPTION

Inside the fireplace chamber, **Kratki's signature ceramic lining** enhances both combustion efficiency and long-term durability. These heat-intensifying ceramics deliver exceptional thermal performance, supporting primary and secondary combustion for a cleaner burn and maximum heat output. By maintaining consistently high temperatures within the combustion chamber, the ceramics make the fireplace easier to operate, improve heat delivery, and significantly reduce soot buildup in the flue system. Lining the chamber with ceramics provides the highest level of protection to the steel structure, extending the lifespan of the fireplace.

The **body of the fireplace** insert is built from high-quality, thick steel, ensuring exceptional resistance to high temperatures. Each unit is precision-welded in a shielded noble gas environment for superior structural integrity and airtight performance. Using advanced laser-cutting and CNC bending technology, every steel component is crafted with accuracy and consistency to guarantee a perfect fit and long-lasting durability.

A large rectangular glass door frames the flames beautifully, while **Kratki's superior heat-resistant glass** and air-wash system help keep the viewing window clear. For improved safety and performance, as well as to increase their lifespan, the heat-resistant glass that Kratki uses is of the highest quality.

The **comfortable handle** features a solid, ergonomic design with a modern aesthetic. Its perforated construction not only enhances the contemporary look but also helps to dissipate heat.

Single air control to regulate the primary airflow.

A **permanent secondary air intake** is provided at the top of the glass door. By maintaining continuous secondary airflow, the fire remains steady even when the main air controls are fully closed - ensuring a consistent, efficient burn within the chamber. This system significantly reduces temperature fluctuations and makes the fireplace easier to run. It also helps keep the fireplace glass clean and reduces soot build-up within the flue system.

Built to deliver lasting warmth and reliability, all Kratki wood-burning fireplaces are backed by a **10-year warranty**, reflecting Kratki's commitment to quality, performance, and longevity.

NOTES